

看板重量(kg)/吊りワイヤー本数 基準表								作成日:2009年 6月 4日		
								ワイヤー:2.0mmφ (SUS304、7X7) フック:SF-20RP(荒川技研工業株)		
								作 成 者 : 小森龍一郎		
長さ \ 高さ	400	450	600	650	750	800	900	1000	1200	1500
1800	3.7/2	4.1/2	5.2/2	5.5/2	6.2/2	6.6/2	7.3/2	8.0/2	11.7/2	14.2/2
2500	5.2/2	5.3/2	7.2/2	7.7/2	8.7/2	9.1/2	10.1/2	11.1/2	16.3/2	19.8/2
2700	5.6/2	6.1/2	7.7/2	8.2/2	9.2/2	9.8/2	10.8/2	11.9/2	17.3/2	21.0/2
3000	6.2/2	6.8/2	8.5/2	9.1/2	10.3/2	10.9/2	12.1/2	13.3/2	19.4/2	23.5/2
3600	7.3/2	8.1/2	10.2/2	10.9/2	12.3/2	13/2	14.4/2	15.8/2	22.9/2	27.8/2
4500	9.2/2	10/2	12.7/2	13.5/2	15.3/2	16.2/2	18/2	20/2	28.5/2	34.5/2
5000	10.2/2	11/2	14/2	15/2	16.9/2	17.9/2	19.8/2	21.8/2	31.5/2	38.2/2
5400	11/2	12/2	15.2/2	16.2/2	18.3/2	19.3/3	21.4/3	23.5/3	34.1/3	41.3/3
6000	12.2/3	13.4/3	16.9/3	18.1/3	20.4/3	21.6/3	24/3	26.3/3	38.2/3	46.3/3
7200	14.7/4	16.1/4	20.3/4	21.7/4	24.5/4	25.9/4	28.7/4	31.5/4	45.8/4	55.5/4
8100	17/4	18.1/4	22.8/4	24.4/4	27.5/4	29.1/4	32.3/4	35.4/4	51.4/4	62.3/4
9000	18.3/4	20.1/4	25.3/4	27.1/4	30.6/4	32.3/4	35.8/4	39.3/4	57/4	69/4
9600	19.6/5	21.5/5	27.1/5	28.9/5	32.7/5	34.6/5	38.3/5	42.1/5	61.1/5	74/5
10800	22.2/5	24/5	30.3/5	32.4/5	36.6/5	38.7/5	42.9/5	47.1/5	68.1/5	82.6/5
12000	24.4/6	26.7/6	33.7/6	36/6	40.7/6	43/6	47.7/6	52.3/6	75.7/6	91.8/6
備 考	両面3.0mm <sup>2</sup> ニヤ、棧木@450 20X30・30X40(H1200以上)、比重:合板0.55、棧木0.40									
	吊りフック許容荷重:50kg(2.0mmφ ワイヤー時)、70kg(2.5mmφ ワイヤー時)					ワイヤー許容荷重:50kg(2.0mmφ )、70kg(2.5mmφ )		荒川技研工業株規定数値		
	複数吊り許容荷重の計算方法:(ワイヤー許容荷重×本数)×0.6							荒川技研工業株規定数値		